

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

# LISTING SERVICE

**LISTING No.** 7125-0785:159 Page 1 of 1

**CATEGORY:** Fire Alarm Devices for the Hearing Impaired

**LISTEE:** Wheelock Inc., 273 Branchport Avenue, Long Branch, NJ, 07740  
Contact: Luy Nguyen (732) 222-6880 Fax (732) 222-5607

**DESIGN:** Synchronized or Non-Synchronized High Intensity Remote Strobe Lights. Models \*RSS-24150C, \*RSS-24177C, RSS-24150CR, RSS-24177CR, RSS-24150W, RSS-24177W, RSS-24185W, \*RSSP-24150C, \*RSSP-24177C, RSSP-24150CR, RSSP-24177CR, RSSP-24150W, RSSP-24177W, RSSP-24185W. Units may be followed by two alpha or numeric characters indicating lettering and product color. Refer to listee's data sheet for additional detailed product description and operation considerations.

**RATING:** Electrical: 24 = 16-33 VDC/VFR  
Flash rate: 60 flashes/minute  
Candela: Wall = 150cd, 177cd, 185cd  
Ceiling = 150cd, 177cd

**INSTALLATION:** In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction. Models with suffix W are for wall mount only. Models with suffix \*CR are for ceiling mount \*round grilles only. All models are for indoor use only.

**MARKING:** Listee's name, model number, electrical/candela rating and UL label.

**APPROVAL:** Listed as strobe lights suitable for the hearing impaired when used with separately listed electrically compatible fire alarm control units. For synchronized strobes, Models SM-12/24, SMX-12/24, DSM-12/24 or DSMX-12/24 Sync Control Module (CSFM Listing No. 7300-0785:132) or PS-12/24-8 Power Unit (CSFM Listing No. 7315-0785:149) must be used.

If the distinctive three-pulse Temporal Pattern Fire Alarm Evacuation Signal (for total evacuation) in accordance with NFPA 72, 1999 Edition is required, the control units must be used with appliances that can generate the temporal pattern signal. Refer to listee's Installation Instructions Manual for details

\*Corrected 03-15-03



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: **MARCH 15, 2003**

*Listing Expires **June 30, 2003***

Authorized By: **DIANE K. AREND, Senior Deputy  
Program Manager**